DECK AND POOL COATING, WHITE PRODUCT NAME: DECK AND POOL COATING, WHITE HMIS CODES: H C F R PRODUCT CODE: 0000000000004200 1 0 0 MANUFACTURER'S NAME: RICHARDS PAINT COMPANY : 200 PAINT STREET, ROCKLEDGE, FL 32955 ADDRESS EMERGENCY PHONE : 800-424-9300 DATE PRINTED : 1/6/2010 INFORMATION PHONE : 321-636-6200 NAME OF PREPARER : RICHARD'S PAINT ======= SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION ======== VAPOR PRESSURE WEIGHT REPORTABLE COMPONENTS CAS NUMBER mm Hg @ TEMP PERCENT _____ *** NO REPORTABLE QUANTITIES OF HAZARDOUS INGREDIENTS ARE PRESENT *** *** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. *** N/A BOILING RANGE: N/A WPG (H2O=8.33)10.61 lb/gl VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER COATING V.O.C.: 69 g/l COATING V.O.C.: 0.57 lb/gl SOLUBILITY IN WATER: SOLUBLE APPEARANCE AND ODOR: N/A FLASH POINT: N/A METHOD USED: N/A FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A EXTINGUISHING MEDIA: Foam, Alcohol Foam, CO2, Dry Chemical, Water Fog SPECIAL FIREFIGHTING PROCEDURES Self-contained breathing apparatus and protective clothing should be worn when fighting fires involving chemicals. If a large amount is involved, evacuate anyone not properly protected. UNUSUAL FIRE AND EXPLOSION HAZARDS Closed containers may explode when exposed to extreme heat. STABILITY: Stable

MATERIAL SAFETY DATA SHEET

Page: 1

CONDITIONS TO AVOID

INCOMPATIBILITY (MATERIALS TO AVOID)

Oxidizing materials can cause reaction.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Carbon dioxide, carbon monoxide, various hydrocarbons.

DECK AND POOL COATING, WHITE

HAZARDOUS POLYMERIZATION: Will Not Occur

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Inhalation: Irritates respiratory passages and eyes very slightly. May cause headache or nausea.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Eye contact: Direct contact irritates slightly with redness and swelling.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin contact: Can dry and defat skin causing cracks, irritation and dermititis.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Ingestion: Can cause gastrointestinal irritation.

HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute: Eyes: Slight iritation with redness. Skin: No adverse effect. Inhalation: Irritates respiratory passage Ingestion: Large amounts may cause digestive discomfort. Chronic: None known.

** CARCINOGENICITY **

NTP CARCINOGEN: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Dermititis, respiratory tract irritation.

EMERGENCY AND FIRST AID PROCEDURES

Inhalation overexposure: Move person to fresh air.If breathing is difficult, administer oxygen. If breathing has stopped give artificial respiration and get medical attention. Eye contact: Flush with large quantities of water for 15 minutes. Skin contact: Wash thoroughly with soap and water. Remove contaminated clothing. Ingestion: Do not induce vomiting, can cause chemical pneumonitis and pulmonary edema. Contact a Physician immediately. If any symptoms persist get medical attention.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area and cover with inert, absorbent material and remove to disposal container. Mop with mild detergents or cleaning solutions. Observe all relevant federal, state and local laws.

WASTE DISPOSAL METHOD

Consult local, state and federal waste regulations before disposing into approved waste landfills. Obey relevant laws. ** DO NOT INCINERATE CLOSED CONTAINERS **

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Handling: No special precautions. Storage: No special precautions. Use reasonable care.

OTHER PRECAUTIONS

- *** BEFORE USING ANY RICHARD'S PAINT MFG PRODUCTS READ THE PRODUCT'S LABEL ***

RESPIRATORY PROTECTION

MATERIAL SAFETY DATA SHEET

DECK AND POOL COATING, WHITE

Not required under normal conditions of use. When spraying this material use in well ventilated area.

VENTILATION

General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below TLV.

PROTECTIVE GLOVES

Gloves may be worn for protection if skin is sensitive. (latex, neoprene, nitrile rubber)

EYE PROTECTION

Use chemical safety glasses, goggles or faceshields for eye protection.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Use protective clothing whenever possible to prevent skin contact.

WORK/HYGIENIC PRACTICES

Eye wash and safety showers in the workplace are recommended.

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by Richard's Paint Manufacturing Co.Inc. to be accurate at the time of preparation. Richard's Paint Manufacturing Co., Inc. does not assume any legal responsibility for use or reliance upon same. ** BEFORE USING ANY PRODUCT READ ITS LABEL **