

RECOMMENDED PRIMER COATINGS

The following Richard's products are recommended primer coatings for this finish coating material. However, recommended Richard's primer coatings are not limited to the products listed below;

- **New Masonry, Pavers & Cementitious Floor Surfaces:**
 - Self-Priming

APPLICATION EQUIPMENT

- **Brush Application:** Apply using quality nylon, polyester or combination nylon/polyester, or a quality natural china bristle brush.
- **Roller Application:** Apply using a 3/8" - 1 1/4" nap synthetic, lamb's wool or mohair roller cover, depending on texture or surface porosity.
- **Airless Spray Application:**
 - **Pump:** Graco – GM3000/495ST Wagner – EP2300
 - **Tip:** 0.013 – 0.015 Reversible
 - **Pressure:** Minimum 2000 psi
 - **Hose:** 1/4 inch (6.3 mm) - 3/8 inch (10 mm)

PACKAGING & WEIGHT PER GALLON

- **Packaging:**

Quarts – 6/case	Gallons – 4/case
2 Gallons – N/A	5 Gallons - Each
- **Weight Per Gallon:** 7.59 lbs.
- **Shelf Life:** Unopened – 2 to 3 Years

CLEAN UP & THINNING INSTRUCTIONS

Clean Up: Clean up any minor spills and spatters immediately with **Xylene**, as well as all painting tools and airless equipment. More serious spills should be contained and removed with inert absorbent material. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state and federal regulations.

Thinning: Stir thoroughly and apply as it comes from the container. Thinning is not necessary. However, if thinning is required, you may add **Xylene**.

WARRANTY & LIMITATIONS

The technical information contained herein is accurate to the best of our knowledge. All warranties are excluded, whether expressed or implied, by operation of law or otherwise, including all implied warranties of merchantability or fitness for a particular purpose. Seller shall not be liable, directly or indirectly, under any circumstances for consequential, incidental, special or any other type of damages arising or resulting for any reason under the sale, handling, or use of goods sold. Seller's liability hereunder, and buyer's exclusive remedy hereunder, for negligence or any other reason, is expressly limited to reimbursement of the purchase price of the materials sold after proof of purchase is provided to the seller. Notice of any alleged failure or defect in the material must be given to the seller in writing by certified U.S. mail within 15 days of noticing the problem. Failure to give the required notice within the time provided constitutes a waiver of any claim. The Manufacturer is not responsible for any misrepresentation made by the Dealer.

REV 01-15

PRODUCT APPLICATION – General

Shield's All PaverSeal Clear Sealer/Finish may be easily applied with a quality brush, roller cover, or airless spray equipment as follows;

- Surfaces to be painted should be completely dry for 24 hours before application.
- For best results, apply by brush or roller to effectively work material into surface pores.
- It is recommended to apply two (2) finish coats to achieve best results.
- Avoid heavy build-up of material.
- When applying by brush, apply a smooth and generous coat application on smaller surface areas, such as painting trim or cutting-in larger surface areas.
- When applying by roller, apply an even and generous coat in a "W" or crisscross motion, avoiding any excessive respreading or reworking.
- During application, always maintain a proper wet edge by brushing or rolling into previously applied coating area.
- When applying by airless spray equipment, use a unit with a minimum of 2000 psi of pressure, with a 0.013" – 0.015" fluid spray tip.
- During spray application, it is recommended to back-roll the surface area to effectively work coating into surface pores, ensure an even coat application and proper adhesion.
- Avoid exterior paint application when weather conditions are threatening, and late in the afternoon when there is a threat of moisture condensing on newly painted surfaces.
- Apply surface and ambient temperatures are above 55° F and below 90° F.

Special Note: Finished Surface May Become Slippery When Wet. A Non-Skid Additive, Such As Richard's #60, Skid Guard May Be Added During Application To Promote A More Anti-Slip Finish.

PRODUCT LIMITATIONS

- Not for use in corrosive or chemical environments.
- Not for use in areas subject to intense heat.
- Not for use on below grade substrates.

PRECAUTIONARY & SAFETY INFORMATION

CAUTIONS: FLAMMABLE! CONTAINS XYLENE AND TOLUENE! Keep away from heat, sparks, and open flames. Prevent build-up of vapors by opening all windows and doors to achieve proper cross-ventilation. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during and until all vapors are gone. **USE WITH ADEQUATE VENTILATION!** Do not breathe dusts, vapors, or spray mists. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor / mist levels are above applicable levels, wear an appropriately fitted respirator, (NIOSH approved), during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eye, skin and clothing. Use chemical safety glasses, goggles, or a face shield for proper eye protection. Wash thoroughly after handling, and before eating or smoking. Close container after each use. **DO NOT TAKE INTERNALLY!** Refer to MSDS for additional health and safety information.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the content herein may be harmful or fatal.

FIRST AID: In case of eye contact, flush immediately with plenty of water for 15 minutes, and get medical attention immediately; for skin contact, wash thoroughly with plenty of soap and water. If you experience difficulty breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN!