



# SAFETY DATA SHEET

RICHARD'S PAINT COMPANY  
PROD. #51

DATE PRINTED: 07/01/2014  
DATE REVISED: 10/07/2013

## SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT CODE:** #51  
**PRODUCT NAME:** SHIELD'S ALL PAVERSEAL CLEAR SEALER FINISH  
**MANUFACTURER'S NAME:** RICHARD'S PAINT COMPANY  
200 PAINT STREET  
ROCKLEDGE, FL 32955

### Telephone Numbers and Websites:

<b>Product Information</b>	(800)-432-0983 <a href="http://www.richardspaint.com">www.richardspaint.com</a>
<b>Medical Emergency – ChemTrec</b>	(800)-434-9300
<b>* Transportation Emergency – ChemTrec</b>	(800)-434-9300
<i>* for Chemical Emergency ONLY (spill, leak, fire, exposure, or accident)</i>	

## SECTION 2 – HAZARDOUS IDENTIFICATION

**SIGNAL WORD:** Danger

### HMIS CODES

Health	2
Flammability	3
Reactivity	0
Personal Protection	

### HEALTH AND PHYSICAL IDENTIFICATION

Combustible liquid coating and vapor. Irritant. Toxic.

ROUTES OF EXPOSURE	TARGET ORGANS
Inhalation: Yes	Blood: Yes
Skin Contact: Yes	Eyes: Yes
Eye Contact: Yes	Kidneys: Yes
Ingestion: Yes	Liver: Yes
	Lungs: Yes
	Central Nervous System: Yes
	Reproductive: No
	Skin: Yes

### EFFECTS OF OVEREXPOSURE

<b>INHALATION:</b>	Avoid breathing vapors or mists. Symptoms may include coughing, sore throat, labored breathing, and chest pain. Central nervous system depression with nausea, dizziness, headache or stupor.
<b>SKIN:</b>	Mildly irritating but not a skin sensitizer. Symptoms may include redness, burning, and swelling of skin.
<b>EYES:</b>	Avoid contact with eyes. Contact with eyes may cause irritation.
<b>INGESTION:</b>	May be harmful if swallowed.
<b>OTHER:</b>	May produce CNS depression. Pre-existing condition of the following organ(s) may be aggravated by the exposure to this material: lungs

### SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Component / Occupational Exposure Limits		CAS No.	% By Weight
* Toluene	OSHA PEL: 200 ppm ACGIH TLV: 100 ppm	108-88-3	39.58
* Xylene	OSHA PEL-TWA: 100 ppm ACGIH TLV: 100 ppm ACGIH TLV-STEL: 150 ppm	1330-20-7	31.35
* Ethylbenzene		100-41-4	7.45

(\*) Indicates toxic chemical (s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

### SECTION 4 – FIRST AID MEASURES

<b>INHALATION:</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Get medical attention.
<b>SKIN CONTACT:</b>	Remove and wash contaminated clothing before re-use. Wash off immediately with soap and plenty of water. If irritation occurs, seek medical attention.
<b>EYE CONTACT:</b>	In case of eye contact, flush the eyes with water for 15 minutes. If contact lenses are worn, quickly remove them then flush the eyes with plenty of water. If irritation persists, have a physician examine the eyes.
<b>INGESTION:</b>	Seek immediate medical attention. Do not induce vomiting. If vomiting occurs spontaneously, keep the head below the hips to prevent aspiration of liquid into the lungs.
<b>NOTE TO PHYSICIAN:</b>	Treat symptomatically.

### SECTION 5 – FIRE FIGHTING MEASURES

<b>Flash Point:</b>	45°F	<b>Method Used:</b>	Setaflash Closed Cup
<b>Explosion Limits:</b>			
<b>Lower (LEL):</b>	0.7%		
<b>Upper (UEL):</b>	10.60%		

<b>FLAMMABILITY CLASSIFICATION:</b>	RED LABEL - Flammable, Flash below 100°F (38°C)
<b>EXTINGUISHING MEDIA:</b>	Carbon dioxide (CO <sub>2</sub> ). Dry chemical. Foam. Water may be ineffective. If area is heavily exposed to fire and if conditions permit, let the fire burn itself out since water may increase the area contaminated. Use dry chemical, CO <sub>2</sub> , water spray or "alcohol" foam.
<b>SPECIFIC METHODS:</b>	If potential for exposure to vapors or products of combustion exists, wear full fire fighting turnout gear and NIOSH approved self-contained breathing apparatus. In the event of fire, cool containers/tanks with water spray. Keep personnel removed from and upwind of fire.
<b>UNUSUAL HAZARDS:</b>	Vapor is heavier than air and can travel considerable distance to a source of ignition and flashback. Toxic fumes may be emitted during combustion or thermal decomposition of this product.

### SECTION 6 – ACCIDENTAL RELEASE MEASURES

<b>PERSONAL PRECAUTIONS:</b>	INFORMATION NOT AVAILABLE.
<b>ENVIRONMENTAL PRECAUTIONS:</b>	Prevent this material from entering sewers and watercourses by diking or impounding the spilled material. Advise authorities if the product has entered or may enter, sewers, watercourses, or extensive land areas.
<b>METHODS FOR CLEANUP:</b>	Soak up with inert absorbent material. Sweep up and shovel into suitable covered containers. Dispose of according to all applicable federal, state and local regulations. Use non-sparking tools (bronze, aluminum, plastic, wood) to clean up spill.

## SECTION 7 – HANDLING AND STORAGE

<b>HANDLING:</b>	Contents are FLAMMABLE. Keep away from heat, sparks and open flame. During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition. Consult NFPA Code. Use approved Bonding and Grounding procedures. Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.
<b>STORAGE CATEGORY:</b>	DOL Storage Class IC

## SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

<b>ENGINEERING CONTROLS:</b>	As required by OSHA, the user (employer) must "monitor and maintain the concentration of all hazardous substances in the air below their occupational exposure limits." Use with adequate ventilation, especially in confined areas. In case of insufficient ventilation, wear suitable respiratory equipment. The product should only be used in areas where all exposed lighting and other sources of ignition have been removed. Electrical equipment should be protected to the appropriate standard. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded and bonded.
<b>RESPIRATORY PROTECTION:</b>	Local exhaust is recommended to ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. If needed, use a NIOSH/MSHA approved respirator equipped with organic vapor cartridges and P100 filters. For emergencies and unknown concentrations, use supplied-air respiratory protection or a positive pressure, self-contained, breathing apparatus (SCBA).
<b>HAND PROTECTION:</b>	Wear solvent-resistant gloves (butyl rubber or neoprene). Gloves should be replaced immediately if signs of degradation are observed.
<b>EYE PROTECTION:</b>	Wear safety glasses with side-shields. If extra protection is required; wear a face-shield over the safety glasses or splash goggles. Face-shields are only effective if worn in addition to safety glasses or splash goggles. An emergency eye wash should be readily available.
<b>SKIN PROTECTION:</b>	Wear a chemical-resistant, butyl-rubber apron and other protective clothing, as deemed appropriate, to avoid skin contact with material. Safety showers should be readily available.
<b>OTHER DATA:</b>	Good personal hygiene and good housekeeping are important. Spilled material may cause the floor or contaminated area to become slippery.

## SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

<b>PHYSICAL STATE:</b>	Liquid
<b>VAPOR DENSITY:</b>	Heavier Than Air
<b>ODOR:</b>	N/A
<b>DENSITY:</b>	7.59 lb/gl.
<b>SPECIFIC GRAVITY:</b>	.91
<b>BOILING POINT:</b>	121°C - 174°C (250°F - 345°F)
<b>EVAPORATION RATE:</b>	Slower Than Ether
<b>VOC LESS WATER:</b>	713 g/l
<b>PERCENT VOLITILE BY VOLUME:</b>	82.08%
<b>Ph:</b>	Not Determined.

## SECTION 10 – STABILITY AND REACTIVITY

<b>CHEMICAL STABILITY:</b>	Stable under recommended storage conditions.
<b>INCOMPATIBILITY:</b>	No data found.
<b>HAZARDOUS DECOMPOSITION PRODUCTS:</b>	Oxides of carbon, including carbon monoxide.
<b>HAZARDOUS POLYMERIZATION:</b>	Hazardous polymerization does not occur.

## SECTION 11 – TOXICOLOGICAL INFORMATION

Ingredient	CAS NO.	LD50 Oral	LD50 Dermal	LC50 Inhalation
ETHYLBENZENE	100-41-4	3500 mg/kg	Rabbit 15354 mg/kg	17.2 mg/L 4 h
TRIMETHYLBENZENE	108-67-8	5000 mg/kg		24 g/m <sup>3</sup> 4 h
TOLUENE	108-88-3	636 mg/kg	Rabbit 8390 mg/kg 12124 mg/kg	12.5 mg/L 4 h > 26700 ppm 1 h
XYLENES	1330-20-7	4300 mg/kg	Rabbit > 1700 mg/kg	47635 mg/L 4 h 5000 ppm 4 h
PETROLEUM MAPHTHA LIGHT AROMATIC	64742-95-6	8400 mg/kg	> 2000 mg/kg	> 5.2 mg/L 4 h 3400 ppm 4 h
BENZENE, 1, 2, 4-TRIMETHYL-	95-63-6	3400 mg/kg	> 3160 mg/kg	18 g/m <sup>3</sup> 4 h
BENZENE, 1-CHLORO-4-(TRIFLOROMETHYL)	98-56-6	13 g/kg	Rabbit > 2 mg/kg	33 mg/L 4 h

<b>CHRONIC TOXICITY:</b>	Toluene (108-88-3) may cause damage to the following organs: blood, kidneys, liver, brain, and central nervous system. Overexposure to toluene has been reported to cause hearing loss.
<b>CARCINOGENIC EFFECTS:</b>	The International Agency for Research on Cancer (IARC) has classified ethyl benzene as a 2-B Possible Human Carcinogen.
<b>MUTAGENIC EFFECTS:</b>	Toluene may affect genetic material.
<b>REPRODUCTIVE TOXICITY:</b>	No data found.

## SECTION 12 – ECOLOGICAL INFORMATION

No Data Available.

## SECTION 13 – DISPOSAL CONSIDERATIONS

<b>METHOD:</b>	As the US Environmental Protection Agency (EPA), state, regional, and other regulatory agencies may have jurisdiction over the disposal of the waste generated, it is incumbent upon the waste generator to learn of and satisfy all of the waste disposal requirements which affect them. US EPA Hazardous Waste Numbers are applicable to the unadulterated product if it enters the "waste stream".
<b>US EPA HAZARDOUS WASTE NUMBERS:</b>	None

## SECTION 14 – TRANSPORT INFORMATION

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

<b>US GROUND (DOT):</b>	5 Liters (1.3 Gallons) and Less may be Classed as LTD, QTY, OR ORM-D. Larger Containers are Regulated as: UN1263, PAINT, 3, PG III, (ERG#128)
<b>DOT (Dept. of Transportation) HAZARDOUS SUBSTANCES &amp; REPORTABLE QUANTITIES:</b>	Ethyl Benzene 1000 lb RQ. Xylenes (isomers and mixture) 100 lb RQ
<b>Bulk Containers May Be Shipped As (check reportable quantities):</b>	RQ, UN1263, PAINT, 3, PG III, (XYLENES (ISOMERS AND MIXTURE)), (ERG#128)
<b>CANADA (TDG):</b>	UN1263, PAINT, 3, PG III, LIMITED QUANTITY, (ERG#128)
<b>IMO:</b>	5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity. UN1263, PAINT, CLASS 3, PG III, (39 C c.c.), EmS F-E, S-E
<b>IATA / ICAO:</b>	UN1263, PAINT, 3, PG III

## SECTION 15 – REGULATORY INFORMATION

<b>SARA 313:</b>	Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical(s) which are subject the reporting requirements of the Act and 40 CFR Part 372:
------------------	---

CHEMICAL COMPONENT	CAS NO.	% by Weight
*** NO REPORTABLE QUANTITIES OF HAZARDOUS INGREDIENTS ARE PRESENT ***		

<b>TSCA 12 b:</b>	All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.
<b>CALIFORNIA PROPOSITION 65:</b>	Warning: This product contains chemicals known to the State of California to cause cancer and birth defects of other reproductive harm.

## SECTION 16 – OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

<b>NON-WARRANTY:</b>	The information presented in this publication is based upon the research and experience of Richard's Paint. No representation or warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. Richard's Paint makes no warranty or representation of any kind, express or implied, including without limitation any warranty or merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by Richard's Paint are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose particular to the buyer is for the buyer to determine. Richard's Paint assumes no responsibility for the selection of products suitable to the particular purposes of any particular buyer. Richard's Paint shall in no event be liable for any special, incidental, or consequential damages.
<b>MSDS STATUS:</b>	Approved
<b>REVISION DATE:</b>	10/07/2013