



PRODUCT DATA SHEET

PROD. #151
LATEX MASONRY BLOCK FILLER



PRODUCT DESCRIPTION



Latex Masonry Block Filler is a premium professional quality interior/exterior ready mixed primer/filler designed to fill small voids and cracks on properly prepared porous cementitious substrates. Excellent hide, coverage and superior adhesion allows for easy application while its durable finish smoothes and levels masonry and concrete surfaces. It is mildew resistant, provides superior priming properties that is ideal for the application of both water and solvent based finish coatings and it is VOC compliant. Mildew Resistant – This paint contains agents that inhibit the growth of mildew on the surface of this paint film.

| PRODUCT FEATURES | PRODUCT USES | PERFORMANCE QUALITIES | VOC COMPLIANCE | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--|-----------------------|----------------|----------|------------------|-----|--------|----------------|--|--|--|------------|-----|------------|-----|-------------|-----|---------------|-----|--------------|----|-------------------|-----|-------------------|-----|-------------------|-----|----------------|-----|
| <ul style="list-style-type: none"> Latex Acrylic Formula Excellent Hide & Coverage Superior Adhesion Fills Small Cracks & Voids Smoothes & Levels Mildew Resistant VOC Compliant Easy To Use | <p><i>Suitable for the following properly prepared surfaces;</i></p> <p>INTERIOR / EXTERIOR</p> <table> <tr> <td>Masonry</td> <td>Brick</td> </tr> <tr> <td>Concrete</td> <td>Precast Concrete</td> </tr> <tr> <td>CMU</td> <td>Stucco</td> </tr> <tr> <td>Concrete Block</td> <td></td> </tr> </table> <p>Great For Both Interior & Exterior Cementitious Surfaces!</p> | Masonry | Brick | Concrete | Precast Concrete | CMU | Stucco | Concrete Block | | <p>Product Quality: Professional</p> <p>Product Use: Interior / Exterior</p> <p>Application: Brush, Roller Cover</p> <p>Product System: Water-Based</p> <p>Finish: Flat</p> | <table> <tr> <td>AIM</td> <td>Yes</td> </tr> <tr> <td>OTC</td> <td>Yes</td> </tr> <tr> <td>CARB</td> <td>Yes</td> </tr> <tr> <td>SCAQMD</td> <td>Yes</td> </tr> <tr> <td>MPI #</td> <td>No</td> </tr> <tr> <td>LEED® 09CI</td> <td>Yes</td> </tr> <tr> <td>LEED® 09NC</td> <td>Yes</td> </tr> <tr> <td>LEED® 09CS</td> <td>Yes</td> </tr> <tr> <td>LEED® H</td> <td>Yes</td> </tr> </table> | AIM | Yes | OTC | Yes | CARB | Yes | SCAQMD | Yes | MPI # | No | LEED® 09CI | Yes | LEED® 09NC | Yes | LEED® 09CS | Yes | LEED® H | Yes |
| Masonry | Brick | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Concrete | Precast Concrete | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| CMU | Stucco | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Concrete Block | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| AIM | Yes | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| OTC | Yes | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| CARB | Yes | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| SCAQMD | Yes | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MPI # | No | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| LEED® 09CI | Yes | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| LEED® 09NC | Yes | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| LEED® 09CS | Yes | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| LEED® H | Yes | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

SURFACE PREPARATION

General: The entire surface area to be painted should be clean, dry, sound, and free from dirt, grease, oils, waxes, mildew, curing agents and any other surface contaminants that may adversely affect the performance of this coating material.

- Remove any loose, scaling, cracked or peeling paint from previously painted surfaces by hand scraping, sanding, wire brushing or by power tool cleaning methods, such as electric sanders or grinders, etc.
- Previously painted surfaces that show signs of serious deterioration should have the existing coating completely removed and treated as a new masonry surface.
- For exterior surfaces, pressure wash the entire surface area using a unit with a minimum of 2000 psi of water pressure. More difficult areas should be hand scraped, sanded, wire brushed and/or power tool cleaned as mentioned above.
- Repair/replace any damaged and/or delaminated cementitious surface areas with the proper patching and/or building materials. All patching materials should be allowed to dry thoroughly before application of paint coatings.
- Sand all rough paint edges smooth to the adjacent surface area.
- NOTE: Allow all new concrete and masonry substrates to dry/cure for a minimum of 30 days before application of any paint coating, and in accordance with industry standards.**

Mildew - Surface areas affected by mildew should be treated with a commercial mildew removal and/or wash product carefully following manufacturer's application and safety directions. Rinse thoroughly with clean water, and allow a minimum of 24 hours to dry thoroughly.

- WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how you can protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-Lead, or log onto www.epa.gov/lead.

PRODUCT ANALYSIS DATA

PIGMENT: 51.14%

VEHICLE: 48.86%

MORE DETAILED PRODUCT ANALYSIS DATA IS AVAILABLE UPON REQUEST.

TECHNICAL DATA

- COLORS:** White
- TINTING:** Not Recommended
- VEHICLE TYPE:** Vinyl Acrylic
- VISCOSITY:** 113 KU ± 3
- GLOSS @ 60°:** Flat / 0 – 5 units
- FLASH POINT:** N/A
- VOC:** Not to Exceed 50 g/l – 0.42 lb/gal
(Meets AIM, OTC, CARB & SCAQMD Standards)
- SOLIDS:** By Volume: 35.68% ± 2%
By Weight: 56.87% ± 2%
- COVERAGE:** 100 – 250 Sq. Ft. / Gal.
(Depending on Application & Surface Porosity.)
- MIL FILM:** Estimated @ 150 Sq. Ft. / Gal.
Wet: 10.7 mils **Dry:** 3.8 mils
- DRY TIME:** (@ 70° F & 50% Relative Humidity)
To Touch: 2 – 4 Hours
Recoat: 8 Hours, or after overnight dry.
- CLEAN UP:** Warm Soapy Water
- THINNING:** Clean Water

