



PRODUCT DATA SHEET
PROD. #6530 SERIES
RICH PRO 6000
INTERIOR ACRYLIC EGGSHELL WALL PAINT



PRODUCT DESCRIPTION



Rich Pro 6000 Interior Acrylic Eggshell Wall Paint is quality high-performance interior eggshell latex paint coating, specifically developed for use by the professional paint contractor. It has been specially formulated to offer ease of application, provide excellent hide and one coat coverage, and excellent touch-up qualities. It offers superior durability, is non-yellowing, and is washable. Its product versatility allows for application to a variety of interior substrates and it is VOC compliant.

PRODUCT FEATURES	PRODUCT USES	PERFORMANCE QUALITIES	VOC COMPLIANCE								
<ul style="list-style-type: none"> Smooth Eggshell Finish Ease Of Application Excellent Hide Good Durability Low V.O.C. One Coat Coverage Excellent Touch-Up Qualities Non-Yellowing Product Versatility 	<p><i>Suitable for the following properly prepared surfaces;</i></p> <p>INTERIOR</p> <table> <tr> <td>Gypsum Drywall</td> <td>Wood Trim</td> </tr> <tr> <td>Plaster</td> <td>Masonry</td> </tr> <tr> <td>Ceilings</td> <td>Concrete</td> </tr> <tr> <td>Wallboard</td> <td>Primed Metal</td> </tr> </table> <p>For Interior Use Only!</p>	Gypsum Drywall	Wood Trim	Plaster	Masonry	Ceilings	Concrete	Wallboard	Primed Metal	<p>Product Quality: Professional / Best</p> <p>Product Use: Interior</p> <p>Application: Brush, Roller Cover, & Airless Spray</p> <p>Product System: Water-Based</p> <p>Finish: Eggshell</p>	<p>AIM Yes</p> <p>OTC Yes</p> <p>CARB Yes</p> <p>SCAQMD Yes</p> <p>MPI # No</p> <p>LEED® 09CI Yes</p> <p>LEED® 09NC Yes</p> <p>LEED® 09CS Yes</p> <p>LEED® H Yes</p>
Gypsum Drywall	Wood Trim										
Plaster	Masonry										
Ceilings	Concrete										
Wallboard	Primed Metal										

SURFACE PREPARATION

General: The entire surface area to be painted should be clean, dry, sound, and free from dirt, grease, oils, waxes, mildew, rust, efflorescence, and any other surface contaminants that may adversely affect the performance of this coating material.

- Remove any loose, scaling, cracked, blistering and peeling paint from previously painted surfaces, as well as loose rust, mil scale or white rust from metal surfaces by hand scraping, sanding, wire brushing, or by power tool cleaning methods, such as electric sanders, grinders, etc.
- Repair/replace any damaged and/or delaminated surface areas such as, nail holes, gouges, cracks, etc. with the properly recommended patching compounds. Allow all patch compounds to dry thoroughly before paint application.
- Sand smooth all rough paint edges and surface repairs to adjacent main surface area.
- To effectively dull existing sheen levels, sand all glossy surfaces.
- Prime and/or spot prime all bare or new surface areas with the Manufacturer's properly specified primer/sealers compatible to the surface type before application of finish coating.

Mildew - Surface areas affected by mildew should be washed with a commercial mildew removal product carefully following manufacturer's application and safety directions. Rinse thoroughly with clean water, and allow a minimum of 24 hours to dry thoroughly.

- WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how you can protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-Lead, or log onto www.epa.gov/lead.

PRODUCT ANALYSIS DATA

PIGMENT: 32.19%

VEHICLE: 67.81%

MORE DETAILED PRODUCT ANALYSIS DATA IS AVAILABLE UPON REQUEST.

TECHNICAL DATA

- COLORS:** White & Tint Bases
 6530 White 6531 Tint Base
 6532 Deep Base 6533-A Accent Base
- TINTING:** Universal Colorants
- VEHICLE TYPE:** Vinyl Acrylic
- VISCOSITY:** 106 KU ± 1
- GLOSS @ 60°:** Eggshell / 5 – 10 units
- FLASH POINT:** N/A
- VOC:** Not to Exceed 50 g/l – 0.42 lb/gal
(Meets AIM, OTC, CARB & SCAQMD Standards)
- SOLIDS:** By Volume: 35.84% ± 2%
 By Weight: 51.81% ± 2%
- COVERAGE:** 300 – 400 Sq. Ft. / Gal.
(Depending on Application & Surface Porosity.)
- MIL FILM:** Estimated @ 350 Sq. Ft. / Gal.
 Wet: 4.6 mils Dry: 1.6 mils
- DRY TIME:** (@ 70° F & 50% Relative Humidity)
 To Touch: 1 – 2 Hours
 Recoat: 4 – 6 Hours, or after overnight.
- CLEAN UP:** Warm Soapy Water
- THINNING:** Clean Water

