



PRODUCT DATA SHEET
PROD. #SG-60
SKID-GUARD NON-SKID ADDITIVE



PRODUCT DESCRIPTION

Richard's Skid-Guard Non-Skid Additive is state-of-the-art polyethylene granules specifically designed as a non-skid additive for all types of floor coatings. Its special formulation provides a much more durable and safe non-skid surface for both interior and exterior floor surfaces than the typical sand type non-skid additives. It will not alter the color and the paint coating, or its overall performance. Once added to the paint coating, these lightweight granules stay suspended much longer than traditional sand texture additives, and they don't break-down as fast, thus offering longer and better overall performance, durability, and product versatility. It can also be added to a variety of wall coatings to add a decorative effect to walls, ceilings and just about any type of surface that needs painting.

PRODUCT FEATURES	PRODUCT USES	PERFORMANCE QUALITIES	VOC COMPLIANCE
<ul style="list-style-type: none"> Lightweight Granules Stays Suspended Excellent Durability Excellent Performance Decorative Product Versatility Easy to Use 	<i>Suitable for the following properly prepared surfaces;</i> INTERIOR / EXTERIOR Concrete Floors Patios Showers Loading Docks Walkways Garage Floors Stairways Balconies Pool Decks Catwalks Wood Decks Int./Ext. Walls Great For Both Interior & Exterior Use!	Product Quality: Premium Product Use: Interior / Exterior Application: Brush, Roller Cover Product System: Texture Additive Finish: Texture	AIM N/A OTC N/A CARB N/A SCAQMD N/A MPI # N/A LEED® 09CI N/A LEED® 09NC N/A LEED® 09CS N/A LEED® H N/A

SURFACE PREPARATION

General: Follow the surface preparation specifications listed on the product label, or product data sheet of the Richard's paint product to be used.

- WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how you can protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-Lead, or log onto www.epa.gov/lead.

PRODUCT ANALYSIS DATA

PIGMENT: 100.00%

VEHICLE: 0.00%

MORE DETAILED PRODUCT ANALYSIS DATA IS AVAILABLE UPON REQUEST.

TECHNICAL DATA

- COLORS:** White Powder
- GRANULE SIZE:** 375 Microns
- VEHICLE TYPE:** N/A
- VISCOSITY:** N/A
- GLOSS @ 60°:** N/A
- FLASH POINT:** N/A
- VOC:** N/A
- SOLIDS:** By Volume: 100.00% ± 2%
By Weight: 100.00% ± 2%
- COVERAGE:** Varies
(Coverage will vary significantly depending on amount of granules added to the finish paint coating and the application method, surface porosity and condition of the surface.)
- MIL FILM:** N/A
- DRY TIME:** N/A
- CLEAN UP:** N/A
- THINNING:** N/A

RECOMMENDED PRIMER COATINGS

Follow the primer recommendations of the finish Richard's product for the particular surface type to be painted as listed below;

- Gypsum Drywall / Plaster
- Wood
- Masonry & Concrete
- Aluminum & Galvanized Metal
- Ferrous & Non-Ferrous Metal

APPLICATION EQUIPMENT

- **Brush Application:** Apply using a quality nylon, polyester, or combination nylon/polyester bristle brush.
- **Roller Application:** Apply using a smooth - medium nap synthetic or lamb's wool roller cover, depending on the texture and surface porosity.
- **Spray Application:**
 - **Pump:** Gas or Electric Airless Sprayer
 - **Pressure:** Minimum 2500 PSI
 - **Tip:** 0.017 – 0.019 Reversible
 - **Hose:** ¼ inch (6.3 mm) - ⅜ inch (10 mm)

PACKAGING & WEIGHT PER GALLON

- **Packaging:** Pints – 6/cs Quarts – 6/cs Gallons – 4/cs
2 Gallons – Each 5 Gallons - Each
- **Weight per Gallon:** 4.50 lbs.

CLEAN UP & THINNING INSTRUCTIONS

Clean Up: Clean up any minor spills and spatters immediately with a broom or vacuum and disposed properly.

PRODUCT APPLICATION – General

Follow the application specifications listed on the product label, or product data sheet of the Richard's paint product to be used as the finish coating.

MIXING INSTRUCTIONS

- Depending on desired texture, normal recommended mixture is 1 pint can of SG-60 to 1 gallon of paint product.
- Stir the paint product thoroughly, and pour into a separate 1.5 or 2 gallon container.
- Add the Skid-Guard to the paint product, stirring granules into the product while pouring.
- Continue to stir granules into the product until thoroughly mixed with the paint product.
- Apply paint product in accordance with products label directions.

PRODUCT LIMITATIONS

- Not for use in corrosive or chemical environments.
- Not for use in areas subject to intense heat.
- Not for use on below grade substrates.

PRECAUTIONARY & SAFETY INFORMATION

CAUTIONS: Avoid prolonged contact with skin, and breathing of dust, vapors and/or spray mists. Causes eye irritation. **USE WITH ADEQUATE VENTILATION!** Ensure fresh air entry during application and drying. If you experience eye water, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriately fitted respirator, (NIOSH approved), during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Use chemical safety glasses, goggles or a face shield for proper eye protection. Wash thoroughly after handling and before eating or smoking. Close container after each use. **DO NOT TAKE INTERNALLY!**

FIRST AID: In case of skin contact, wash thoroughly with plenty of warm soapy water. For eye contact, flush with plenty of water for 15 minutes and get medical attention immediately. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting, get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN!

WARRANTY & LIMITATIONS

The technical information contained herein is accurate to the best of our knowledge. All warranties are excluded, whether expressed or implied, by operation of law or otherwise, including all implied warranties of merchantability or fitness for a particular purpose. Seller shall not be liable, directly or indirectly, under any circumstances for consequential, incidental, special or any other type of damages arising or resulting for any reason under the sale, handling, or use of goods sold. Seller's liability hereunder, and buyer's exclusive remedy hereunder, for negligence or any other reason, is expressly limited to reimbursement of the purchase price of the materials sold after proof of purchase is provided to the seller. Notice of any alleged failure or defect in the material must be given to the seller in writing by certified U.S. mail within 15 days of noticing the problem. Failure to give the required notice within the time provided constitutes a waiver of any claim. The Manufacturer is not responsible for any misrepresentation made by the Dealer.