

# SAFETY DATA SHEET




## 1. PRODUCT AND COMPANY IDENTIFICATION

|                      |  |
|----------------------|--|
| <b>Product Name:</b> | PAINTER'S PRIDE LATEX FLAT DRYFALL BLACK |
| <b>Product Code:</b> | 5-2010                                   |
| <b>Product Use:</b>  | Paint                                    |

**Manufacturer**  
Richard's Paint  
200 Paint Street  
Rockledge, Florida,  
800-432-0983

**24 Hour Emergency Telephone Number**  
CHEMTEL (US): (800)255-3924  
CHEMTEL (International): (813)248-0585

## 2. HAZARDS IDENTIFICATION

|   |   |
|---|---|
| <b>Classification:</b>                              | This material is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)<br>Skin Sensitization: Category 1<br>Carcinogenicity: Category 2  |
| <b>Signal Word:</b>                                 | Warning   |
| <b>Pictograms:</b>                                  |    |
| <b>Hazard Statements:</b>                           | H317: May cause an allergic skin reaction<br>H351: Suspected of causing cancer  |
| <b>Prevention<br/>Precautionary<br/>Statements:</b> | P201: Obtain special instructions before use<br>P202: Do not handle until all safety precautions have been read and understood<br>P261: Avoid breathing dust/fumes/gas/mist/vapors/spray<br>P272: Contaminated work clothing should not be allowed out of the workplace<br>P280: Wear protective gloves/protective clothing/eye protection/face protection<br>P281: Use personal protective equipment as required |

|   |  |
|---|--|
| <b>Response<br/>Precautionary<br/>Statements:</b> | P302+352: IF ON SKIN: Wash with plenty of water<br>P308+313: IF exposed: Call a POISON CENTER or doctor/physician<br>P333+313: If skin irritation or a rash occurs: Get medical<br>advice/attention<br>P363: Wash contaminated clothing before reuse |
| <b>Storage<br/>Precautionary<br/>Statements:</b>  | P405: Store locked up  |
| <b>Disposal<br/>Precautionary<br/>Statements:</b> | P501: Dispose of contents/container to an approved waste disposal plant  |
| <b>Hazards Not<br/>Otherwise<br/>Classified:</b>  | May cause allergic skin reaction   |

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name                            | Weight %   | CAS Number  |
|--|------------|-------------|
| Calcium carbonate                        | 20% to 30% | 1317-65-3   |
| Talc                                     | 1% to 5%   | 14807-96-6  |
| Carbon black                             | 1% to 5%   | 1333-86-4   |
| Isopropyl alcohol                        | 1% to 5%   | 67-63-0     |
| Propylene glycol butyl ether             | 0% to 1%   | 5131-66-8   |
| Texanol ester alcohol                    | 0% to 1%   | 25265-77-4  |
| Nonylphenol polyethylene glycol<br>ether | 0% to 1%   | 127087-87-0 |
| Crystalline silica                       | 0% to 1%   | 14808-60-7  |
| 4,4-dimethyloxazolidine                  | 0% to 1%   | 51200-87-4  |

### 4. FIRST AID MEASURES

|   |   |
|---|---|
| <b>General Advice:</b>                      | No hazards requiring special first aid measures   |
| <b>Eyes:</b>                                | Remove contact lenses, if applicable. Flush eyes with water for at least 10 minutes. Keep eyes wide open while flushing. Consult a physician if symptoms persist. |
| <b>Skin:</b>                                | Remove contaminated clothing. Flush affected area with soap and water. Consult a physician if irritation persists. Wash contaminated clothing before re-use.      |
| <b>Ingestion:</b>                           | Remove dentures if applicable and wash out mouth with water. Drink large amounts of water. Consult a physician if symptoms persist.                               |
| <b>Inhalation:</b>                          | Move to fresh air. If not breathing, give artificial respiration and consult a physician immediately. Consult a physician if symptoms persist.                    |
| <b>Most Important<br/>Symptoms/Effects:</b> | May cause allergic skin reaction  |
| <b>Notes to Physician:</b>                  | Treat symptomatically   |

### 5. FIRE FIGHTING MEASURES

|  |  |
|--|--|
| <b>Suitable<br/>Extinguishing<br/>Media:</b> | Use measures suitable to the circumstances and environment |
|--|--|

|                                      |   |
|--------------------------------------|---|
| <b>Precautions for Firefighters:</b> | Wear self-contained breathing apparatus and protective gear   |
| <b>Specific Hazards:</b>             | Sealed containers may rupture if exposed to high temperatures |

## 6. ACCIDENTAL RELEASE MEASURES

|                              |  |
|------------------------------|--|
| <b>Personal Precautions:</b> | Use proper personal protective equipment. Avoid contact with skin, eyes, and clothing. Avoid breathing vapors. |
| <b>Other Precautions:</b>    | If safe to do so, prevent additional spillage  |
| <b>Clean-Up Method:</b>      | Soak up with non-combustible absorbent material. Dispose of used absorbent in suitable containers.             |

## 7. HANDLING AND STORAGE

|                                |   |
|--------------------------------|---|
| <b>Handling Precautions:</b>   | Avoid contact with skin, eyes, and clothing. Avoid breathing vapors, mists, or dust. Wear respiratory equipment if ventilation is insufficient. |
| <b>Storage Precautions:</b>    | Keep container upright, properly labeled, tightly closed, and out of reach of children in a cool, dry, well-ventilated area.                    |
| <b>Incompatible Materials:</b> | None  |

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

|                                |                               |                       |
|--------------------------------|-------------------------------|-----------------------|
| Calcium carbonate(1317-65-3)   |                               |                       |
| NIOSH TWA:                     | 5 mg/m3 (respirable fraction) | 10 mg/m3 (total dust) |
| OSHA PEL:                      | 5 mg/m3 (respirable fraction) | 15 mg/m3 (total dust) |
| Carbon black(1333-86-4)        |                               |                       |
| ACGIH TWA:                     | 3 mg/m3                       | --                    |
| NIOSH TWA:                     | 0.1 mg/m3                     | --                    |
| OSHA TWA:                      | 3.5 mg/m3                     | --                    |
| Crystalline silica(14808-60-7) |                               |                       |
| ACGIH TWA:                     | .025 mg/m3                    | --                    |
| NIOSH TWA:                     | .05 mg/m3                     | --                    |
| OSHA TWA:                      | 10 mg/m3/%SiO2+2              | 250 mppcf/%SiO2+5     |
| Isopropyl alcohol(67-63-0)     |                               |                       |
| ACGIH STEL:                    | 400 ppm                       | --                    |
| ACGIH TWA:                     | 200 ppm                       | --                    |
| NIOSH ST:                      | 500 ppm                       | 1225 mg/m3            |
| NIOSH TWA:                     | 400 ppm                       | 980 mg/m3             |
| OSHA TWA:                      | 400 ppm                       | 980 mg/m3             |
| Talc(14807-96-6)               |                               |                       |
| ACGIH TWA:                     | 2 mg/m3                       | --                    |
| NIOSH TWA:                     | 2 mg/m3                       | --                    |
| OSHA TWA:                      | 20 mppcf                      | --                    |

|                              |   |
|------------------------------|---|
| <b>Engineering Measures:</b> | Maintain adequate ventilation to keep exposure to airborne contaminants at safe levels. Use explosion-proof equipment.  |
| <b>Hygiene Measures:</b>     | No eating, drinking, or smoking while in use. Avoid contact with skin, eyes, and clothing. Wash hands, forearms, and face after handling. Wash contaminated clothing before re-use. |
| <b>Eye/Face Protection:</b>  | Safety glasses/goggles  |
| <b>Skin Protection:</b>      | Protective gloves and protective clothing   |

|                                |  |
|--------------------------------|--|
| <b>Respiratory Protection:</b> | Respiratory equipment if ventilation is inadequate |
|--------------------------------|--|

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|   |                          |
|---|--------------------------|
| <b>Physical State:</b>                      | Liquid                   |
| <b>Color:</b>                               | Black                    |
| <b>Odor:</b>                                | Little to none           |
| <b>Odor Threshold:</b>                      | No information available |
| <b>pH:</b>                                  | 8.5-9.5                  |
| <b>Melting Point (°F):</b>                  | No information available |
| <b>Boiling Point (°F):</b>                  | No information available |
| <b>Flash Point (°F):</b>                    | >141                     |
| <b>Flash Point Method:</b>                  | No information available |
| <b>Evaporation Rate:</b>                    | No information available |
| <b>Flammability (Solid/Gas):</b>            | No information available |
| <b>Flammability Limits:</b>                 | No information available |
| <b>Vapor Pressure (mm Hg):</b>              | No information available |
| <b>Vapor Density:</b>                       | No information available |
| <b>Specific Gravity:</b>                    | No information available |
| <b>% Solubility in Water:</b>               | No information available |
| <b>Octanol/Water Partition Coefficient:</b> | No information available |
| <b>Auto-Ignition Temperature (°F):</b>      | No information available |
| <b>Decomposition Temperature (°F):</b>      | No information available |
| <b>Viscosity (KU):</b>                      | 95-99                    |
| <b>Volatile Organic Compounds (g/L):</b>    | 120                      |

## 10. STABILITY AND REACTIVITY

|  |  |
|--|--|
| <b>Reactivity:</b>                         | Not applicable                         |
| <b>Possibility of Hazardous Reactions:</b> | None under normal conditions of use    |
| <b>Hazardous Decomposition Products:</b>   | None under normal conditions of use    |
| <b>Stability:</b>                          | Stable under normal storage conditions |
| <b>Incompatible Materials:</b>             | None                                   |
| <b>Conditions to Avoid:</b>                | Freezing                               |

## 11. TOXICOLOGICAL INFORMATION

|  |                 |
|--|-----------------|
| Carbon black(1333-86-4)                            |                 |
| Dermal LD50 (rabbit):                              | >3000 mg/kg     |
| Oral LD50 (rat):                                   | >8000 mg/kg     |
| Isopropyl alcohol(67-63-0)                         |                 |
| Dermal LD50 (rabbit):                              | 12800 mg/kg     |
| Inhalation LC50 (rat, 8 hrs):                      | 16000 ppm       |
| Oral LD50 (rat):                                   | 5045 mg/kg      |
| Nonylphenol polyethylene glycol ether(127087-87-0) |                 |
| Dermal LD50 (rabbit):                              | 2000-2991 mg/kg |
| Inhalation LC50 (rat, 4 hrs):                      | 1.15 mg/L       |
| Oral LD50 (rat):                                   | 960-3980 mg/kg  |
| Propylene glycol butyl ether(5131-66-8)            |                 |
| Oral LD50 (rat):                                   | 5009 mg/kg      |
| Texanol ester alcohol(25265-77-4)                  |                 |
| Dermal LD50 (rabbit):                              | 15200 mg/kg     |
| Oral LD50 (rat):                                   | 6500 mg/kg      |

|                                    |                                       |
|------------------------------------|---------------------------------------|
| <b>Primary Routes of Exposure:</b> | Eye contact, skin contact, inhalation |
| <b>Acute Toxicity:</b>             | No information available              |

|  |   |
|--|---|
| <b>Exposure Effects</b>                  |   |
| <b>Eye Contact:</b>                      | Irritation  |
| <b>Skin Contact:</b>                     | Irritation, drying                                      |
| <b>Inhalation:</b>                       | Irritation of respiratory system                        |
| <b>Ingestion:</b>                        | Gastrointestinal irritation, diarrhea, nausea, vomiting |
| <b>Target Organ (Single Exposure):</b>   | No information available                                |
| <b>Target Organ (Repeated Exposure):</b> | No information available                                |
| <b>Sensitization:</b>                    | No information available                                |
| <b>Carcinogenicity:</b>                  | No information available                                |
| <b>Mutagenicity:</b>                     | No information available                                |
| <b>Reproductive Toxicity:</b>            | No information available                                |
| <b>Other:</b>                            | No information available                                |

## 12. ECOLOGICAL INFORMATION

|  |             |
|--|-------------|
| Carbon black(1333-86-4)                            |             |
| LC50 (zebra fish, 96 hrs):                         | >1000 mg/L  |
| Static EC50 (green algae, 72 hrs):                 | >10000 mg/L |
| Static EC50 (water flea, 24 hrs):                  | >5400 mg/L  |
| Isopropyl alcohol(67-63-0)                         |             |
| EC50 (algae, 24 hrs):                              | >1000 mg/L  |
| EC50 (green algae, 72 hrs):                        | 2000 mg/L   |
| EC50 (water flea, 24 hrs):                         | 5102 mg/L   |
| Immobilization EC50 (water flea, 24 hrs):          | 6851 mg/L   |
| LC50 (fathead minnow, 96 hrs):                     | 9640 mg/L   |
| Nonylphenol polyethylene glycol ether(127087-87-0) |             |
| BCF:   | 5.9-48      |

|                                       |               |
|---------------------------------------|---------------|
| Biodegradability:                     | <60%          |
| EC50 (water flea, 48 hrs):            | 9.3-21.4 mg/L |
| IC50 (bacteria, 16 hrs):              | >1000 mg/L    |
| LC50 (fathead minnow, 96 hrs):        | 3.8-6.2 mg/L  |
| Texanol ester alcohol(25265-77-4)     |               |
| Biodegradability (aerobic, 28 days):  | >98%          |
| Static EC50 (green algae, 72 hrs):    | 18.4 mg/L     |
| Static EC50 (water flea, 48 hrs):     | 147.8 mg/L    |
| Static LC50 (fathead minnow, 96 hrs): | 33 mg/L       |

|                                   |   |
|-----------------------------------|---|
| <b>Ecotoxicological Effects:</b>  | The environmental impact of this substance has not been fully evaluated |
| <b>Persistence/Degradability:</b> | No information available  |
| <b>Bioaccumulative Potential:</b> | No information available  |
| <b>Environmental Mobility:</b>    | No information available  |
| <b>Other Effects:</b>             | No information available  |

### 13. DISPOSAL CONSIDERATIONS

|                         |  |
|-------------------------|--|
| <b>Disposal Method:</b> | Dispose of in accordance with federal, state, provincial, and local regulations. |
|-------------------------|--|

### 14. TRANSPORT INFORMATION

|                   |               |
|-------------------|---------------|
| <b>DOT:</b>       | Not regulated |
| <b>ICAO/IATA:</b> | Not regulated |
| <b>IMDG/IMO:</b>  | Not regulated |

### 15. REGULATORY INFORMATION

|                           |                                     |
|---------------------------|-------------------------------------|
| <b>TSCA (US):</b>         | All components are listed or exempt |
| <b>DSL/NDSL (Canada):</b> | All components are listed or exempt |

|   |     |
|---|-----|
| <b><u>311/312 Hazard Categories</u></b> |     |
| <b>Fire:</b>                            | No  |
| <b>Pressure Generating:</b>             | No  |
| <b>Reactivity:</b>                      | No  |
| <b>Acute:</b>                           | Yes |
| <b>Chronic:</b>                         | Yes |

|                                  |   |
|----------------------------------|---|
| <b><u>CERCLA Section 302</u></b> |   |
| <b>Reportable Quantities:</b>    | This material does not contain any hazardous components listed on Table 302.4 |

|                      |                   |                     |                         |
|----------------------|-------------------|---------------------|-------------------------|
| <b>SARA 313</b>      |                   |                     |                         |
| <b>Chemical Name</b> | <b>CAS Number</b> | <b>Max Weight %</b> | <b>de minimis limit</b> |


|                   |         |   |     |
|-------------------|---------|---|-----|
| Isopropyl alcohol | 67-63-0 | 5 | 1.0 |
|-------------------|---------|---|-----|

| <b>State Right-to-Know</b>            |                   |           |           |           |           |
|---------------------------------------|-------------------|-----------|-----------|-----------|-----------|
| <b>Chemical Name</b>                  | <b>CAS Number</b> | <b>MA</b> | <b>NJ</b> | <b>PA</b> | <b>RI</b> |
| Calcium carbonate                     | 1317-65-3         | X         | X         | X         | X         |
| Talc                                  | 14807-96-6        | X         | X         | X         | X         |
| Carbon black                          | 1333-86-4         | X         | X         | X         | X         |
| Isopropyl alcohol                     | 67-63-0           | X         | X         | X         | X         |
| Propylene glycol butyl ether          | 5131-66-8         |           | X         | X         |           |
| Texanol ester alcohol                 | 25265-77-4        |           | X         | X         |           |
| Nonylphenol polyethylene glycol ether | 127087-87-0       |           | X         | X         |           |
| Crystalline silica                    | 14808-60-7        |           | X         | X         | X         |
| 4,4-dimethyloxazolidine               | 51200-87-4        |           | X         | X         |           |

|                                   |   |
|-----------------------------------|---|
| <b>California Proposition 65:</b> | This product contains small amounts of materials known to the state of California to cause cancer or reproductive harm. |
|-----------------------------------|---|

**16. OTHER INFORMATION**

| <b>HMIS RATING</b>   |    |
|----------------------|----|
| Health:              | 1* |
| Flammability:        | 0  |
| Reactivity:          | 0  |
| Personal Protection: | -- |



PPE rating has been left intentionally blank. Choose appropriate PPE based upon actual conditions of use.

|                            |   |
|----------------------------|---|
| <b>Revision Indicator:</b> | Revised 4/21/2021   |
| <b>Disclaimer:</b>         | The information contained in this Safety Data Sheet (SDS) is provided in good faith and is believed to be accurate as of the effective date listed. The information applies only to the product as provided and may not be valid if combined with other materials. No warranty is implied or given. The user is responsible for complying with all applicable laws and regulations. |