

# SAFETY DATA SHEET



## 1854 - THOR ULTRA PREMIUM WB ACRYLIC SEMI-GLOSS BLACK


### 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product Name:</b>	1854 - THOR ULTRA PREMIUM WB ACRYLIC SEMI-GLOSS BLACK
<b>Product Code:</b>	1854
<b>Product Use:</b>	Paint

**Manufacturer**  
Richard's Paint  
200 Paint Street  
Rockledge, Florida,  
800-432-0983

**24 Hour Emergency Telephone Number**  
CHEMTEL (US): (800)255-3924  
CHEMTEL (International): (813)248-0585

### 2. HAZARDS IDENTIFICATION

<b>Classification:</b>	This material is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) Skin Sensitization: Category 1 Carcinogenicity: Category 2
<b>Signal Word:</b>	Warning
<b>Pictograms:</b>	
<b>Hazard Statements:</b>	H317: May cause an allergic skin reaction H351: Suspected of causing cancer
<b>Prevention Precautionary Statements:</b>	P201: Obtain special instructions before use P202: Do not handle until all safety precautions have been read and understood P261: Avoid breathing dust/fumes/gas/mist/vapors/spray P272: Contaminated work clothing should not be allowed out of the workplace P280: Wear protective gloves/protective clothing/eye protection/face protection P281: Use personal protective equipment as required
<b>Response Precautionary Statements:</b>	P302+352: IF ON SKIN: Wash with plenty of water P308+313: IF exposed: Call a POISON CENTER or doctor/physician P333+313: If skin irritation or a rash occurs: Get medical advice/attention P363: Wash contaminated clothing before reuse

<b>Storage Precautionary Statements:</b>	P405: Store locked up
<b>Disposal Precautionary Statements:</b>	P501: Dispose of contents/container to an approved waste disposal plant
<b>Hazards Not Otherwise Classified:</b>	May cause allergic skin reaction

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Weight %	CAS Number
Texanol ester alcohol	1% to 5%	25265-77-4
Di(ethylene glycol) ethyl ether	1% to 5%	111-90-0
Kaolin	1% to 5%	1332-58-7
Carbon black	1% to 5%	1333-86-4
Propylene glycol	0% to 1%	57-55-6
Tri(ethylene glycol) bis(2-ethylhexanoate)	0% to 1%	94-28-0
Ammonium hydroxide	0% to 1%	1336-21-6
4,4-dimethyloxazolidine	0% to 1%	51200-87-4
Alcohols, C12-15, ethoxylated	0% to 1%	68131-39-5
Diethylene glycol butyl ether	0% to 1%	112-34-5
Distillates (petroleum), light distillate hydrotreating process, low-boiling	0% to 1%	68410-97-9

### 4. FIRST AID MEASURES

<b>General Advice:</b>	No hazards requiring special first aid measures
<b>Eyes:</b>	Remove contact lenses, if applicable. Flush eyes with water for at least 10 minutes. Keep eyes wide open while flushing. Consult a physician if symptoms persist.
<b>Skin:</b>	Remove contaminated clothing. Flush affected area with soap and water. Consult a physician if irritation persists. Wash contaminated clothing before re-use.
<b>Ingestion:</b>	Remove dentures if applicable and wash out mouth with water. Drink large amounts of water. Consult a physician if symptoms persist.
<b>Inhalation:</b>	Move to fresh air. If not breathing, give artificial respiration and consult a physician immediately. Consult a physician if symptoms persist.
<b>Most Important Symptoms/Effects:</b>	May cause allergic skin reaction
<b>Notes to Physician:</b>	Treat symptomatically

### 5. FIRE FIGHTING MEASURES

<b>Suitable Extinguishing Media:</b>	Use measures suitable to the circumstances and environment
<b>Precautions for Firefighters:</b>	Wear self-contained breathing apparatus and protective gear
<b>Specific Hazards:</b>	Sealed containers may rupture if exposed to high temperatures

## 6. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions:</b>	Use proper personal protective equipment. Avoid contact with skin, eyes, and clothing. Avoid breathing vapors.
<b>Other Precautions:</b>	If safe to do so, prevent additional spillage
<b>Clean-Up Method:</b>	Soak up with non-combustible absorbent material. Dispose of used absorbent in suitable containers.

## 7. HANDLING AND STORAGE

<b>Handling Precautions:</b>	Avoid contact with skin, eyes, and clothing. Avoid breathing vapors, mists, or dust. Wear respiratory equipment if ventilation is insufficient.
<b>Storage Precautions:</b>	Keep container upright, properly labeled, tightly closed, and out of reach of children in a cool, dry, well-ventilated area.
<b>Incompatible Materials:</b>	None

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ammonium hydroxide(1336-21-6)		
ACGIH STEL:	35 ppm	--
ACGIH TWA:	25 ppm	--
NIOSH ST:	35 ppm	27 mg/m3
NIOSH TWA:	25 ppm	18 mg/m3
Carbon black(1333-86-4)		
ACGIH TWA:	3 mg/m3	--
NIOSH TWA:	0.1 mg/m3	--
OSHA TWA:	3.5 mg/m3	--
Di(ethylene glycol) ethyl ether(111-90-0)		
WEEL TWA:	25 ppm	--
Diethylene glycol butyl ether(112-34-5)		
ACGIH TWA:	10 ppm	--
Distillates (petroleum), light distillate hydrotreating process, low-boiling(68410-97-9)		
ACGIH TWA:	200 ppm	--
Kaolin(1332-58-7)		
ACGIH TWA: 2 mg/m3	NIOSH TWA: 5 mg/m3	OSHA TWA: 5 mg/m3
Propylene glycol(57-55-6)		
WEEL TWA:	10 mg/m3	--

<b>Engineering Measures:</b>	Maintain adequate ventilation to keep exposure to airborne contaminants at safe levels. Use explosion-proof equipment.
<b>Hygiene Measures:</b>	No eating, drinking, or smoking while in use. Avoid contact with skin, eyes, and clothing. Wash hands, forearms, and face after handling. Wash contaminated clothing before re-use.
<b>Eye/Face Protection:</b>	Safety glasses/goggles
<b>Skin Protection:</b>	Protective gloves and protective clothing
<b>Respiratory Protection:</b>	Respiratory equipment if ventilation is inadequate

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical State:</b>	Liquid
------------------------	--------

<b>Color:</b>	Black
<b>Odor:</b>	Little to none
<b>Odor Threshold:</b>	No information available
<b>pH:</b>	9.0-9.4
<b>Melting Point (°F):</b>	No information available
<b>Boiling Point (°F):</b>	No information available
<b>Flash Point (°F):</b>	>141
<b>Flash Point Method:</b>	No information available
<b>Evaporation Rate:</b>	No information available
<b>Flammability (Solid/Gas):</b>	No information available
<b>Flammability Limits:</b>	No information available
<b>Vapor Pressure (mm Hg):</b>	No information available
<b>Vapor Density:</b>	No information available
<b>Specific Gravity:</b>	No information available
<b>% Solubility in Water:</b>	No information available
<b>Octanol/Water Partition Coefficient:</b>	No information available
<b>Auto-Ignition Temperature (°F):</b>	No information available
<b>Decomposition Temperature (°F):</b>	No information available
<b>Viscosity (KU):</b>	95-99
<b>Volatile Organic Compounds (g/L):</b>	249

## 10. STABILITY AND REACTIVITY

<b>Reactivity:</b>	Not applicable
<b>Possibility of Hazardous Reactions:</b>	None under normal conditions of use
<b>Hazardous Decomposition Products:</b>	None under normal conditions of use
<b>Stability:</b>	Stable under normal storage conditions
<b>Incompatible Materials:</b>	None
<b>Conditions to Avoid:</b>	Freezing

## 11. TOXICOLOGICAL INFORMATION

Alcohols, C12-15, ethoxylated(68131-39-5)	
Dermal LD50 (rabbit):	>2000 mg/kg
Oral LD50 (rat):	1650-2000 mg/kg
Carbon black(1333-86-4)	
Dermal LD50 (rabbit):	>3000 mg/kg
Oral LD50 (rat):	>8000 mg/kg

Di(ethylene glycol) ethyl ether(111-90-0)	
Dermal LD50 (rabbit):	9143 mg/kg
Inhalation LC50 (rat):	>200 mg/L
Oral LD50 (rat):	10502 mg/kg
Diethylene glycol butyl ether(112-34-5)	
Dermal LD50 (rabbit):	2764 mg/kg
Oral LD50 (rat):	7291 mg/kg
Distillates (petroleum), light distillate hydrotreating process, low-boiling(68410-97-9)	
Dermal LD50 (rabbit):	>2000 mg/kg
Inhalation LC50 (rat, 4 hrs):	>5.2 mg/L
Oral LD50 (rat):	5.17 g/kg
Propylene glycol(57-55-6)	
Dermal LD50 (rabbit):	20800 mg/kg
Intramuscular LD50 (rat)	14 g/kg
Intraperitoneal LD50 (mouse):	9718 mg/kg
Intraperitoneal LD50 (rat):	6660 mg/kg
Intravenous LD50 (dog):	26 g/kg
Intravenous LD50 (mouse):	6630 mg/kg
Intravenous LD50 (rabbit):	6500 mg/kg
Intravenous LD50 (rat):	6423 mg/kg
Oral LD50 (rat):	20000 mg/kg
Subcutaneous LD50 (mouse):	17370 mg/kg
Subcutaneous LD50 (rat):	22500 mg/kg
Texanol ester alcohol(25265-77-4)	
Dermal LD50 (rabbit):	15200 mg/kg
Oral LD50 (rat):	6500 mg/kg
Tri(ethylene glycol) bis(2-ethylhexanoate)(94-28-0)	
Dermal LD50 (rat):	>2000 mg/kg
Inhalation LC50 (rat, 4 hrs):	>2 mg/L
Oral LD50 (rat):	>2000 mg/kg

<b>Primary Routes of Exposure:</b>	Eye contact, skin contact, inhalation
<b>Acute Toxicity:</b>	No information available

<b>Exposure Effects</b>	
<b>Eye Contact:</b>	Irritation
<b>Skin Contact:</b>	Irritation, drying
<b>Inhalation:</b>	Irritation of respiratory system
<b>Ingestion:</b>	Gastrointestinal irritation, diarrhea, nausea, vomiting
<b>Target Organ (Single Exposure):</b>	No information available
<b>Target Organ (Repeated Exposure):</b>	No information available
<b>Sensitization:</b>	No information available
<b>Carcinogenicity:</b>	No information available
<b>Mutagenicity:</b>	No information available
<b>Reproductive Toxicity:</b>	No information available
<b>Other:</b>	No information available

## 12. ECOLOGICAL INFORMATION

Alcohols, C12-15, ethoxylated(68131-39-5)	
Acute EC50 (algae, 72 hrs):	10-100 mg/L
Acute EC50 (water flea, 48 hrs):	5-10 mg/L
Acute LC50 (fish, 96 hrs):	5-10 mg/L
Carbon black(1333-86-4)	
LC50 (zebra fish, 96 hrs):	>1000 mg/L
Static EC50 (green algae, 72 hrs):	>10000 mg/L
Static EC50 (water flea, 24 hrs):	>5400 mg/L
Di(ethylene glycol) ethyl ether(111-90-0)	
LC50 (fathead minnow, 96 hrs):	9650 mg/L
LC50 (water flea, 48 hrs):	3340 mg/L
Diethylene glycol butyl ether(112-34-5)	
Biodegradability (aerobic, 28 days):	91.7%
LC50 (Pseudomonas putida, 16 hrs):	1170 mg/L
Static EC50 (Scenedesmus subspicatus, 96 hrs):	>100 mg/L
Static EC50 (water flea, 48 hrs):	>100 mg/L
Static LC50 (Lepomis macrochirus, 96 hrs):	1300 mg/L
Distillates (petroleum), light distillate hydrotreating process, low-boiling(68410-97-9)	
Acute EC50 (algae, 72 hrs):	1-10 mg/L
Acute EC50 (water flea, 48 hrs):	1-10 mg/L
Acute LC50 (fish, 96 hrs):	1-10 mg/L
Chronic NOEL (fish, 14 days):	2.6 mg/L
Chronic NOEL (water flea, 21 days):	2.6 mg/L
Propylene glycol(57-55-6)	
EC50 (water flea, 48 hrs):	>10000 mg/L
Mortality NOEC (fathead minnow, 96 hrs):	52930 mg/L
Mortality NOEC (water flea, 48 hrs):	13020 mg/L
Texanol ester alcohol(25265-77-4)	
Biodegradability (aerobic, 28 days):	>98%
Static EC50 (green algae, 72 hrs):	18.4 mg/L
Static EC50 (water flea, 48 hrs):	147.8 mg/L
Static LC50 (fathead minnow, 96 hrs):	33 mg/L
Tri(ethylene glycol) bis(2-ethylhexanoate)(94-28-0)	
Biodegradability (aerobic, 28 days):	92%
Static EC50 (green algae, 72 hrs):	>55.9 mg/L
Static EC50 (water flea, 48 hrs):	38.7 mg/L
Static LC50 (fathead minnow, 96 hrs):	>97 mg/L

<b>Ecotoxicological Effects:</b>	The environmental impact of this substance has not been fully evaluated
<b>Persistence/Degradability:</b>	No information available
<b>Bioaccumulative Potential:</b>	No information available
<b>Environmental Mobility:</b>	No information available
<b>Other Effects:</b>	No information available

### 13. DISPOSAL CONSIDERATIONS

<b>Disposal Method:</b>	Dispose of in accordance with federal, state, provincial, and local regulations.
-------------------------	--

### 14. TRANSPORT INFORMATION

<b>DOT:</b>	Not regulated
<b>ICAO/IATA:</b>	Not regulated
<b>IMDG/IMO:</b>	Not regulated

## 15. REGULATORY INFORMATION

<b>TSCA (US):</b>	All components are listed or exempt
<b>DSL/NDSL (Canada):</b>	All components are listed or exempt

<b>311/312 Hazard Categories</b>	
<b>Fire:</b>	No
<b>Pressure Generating:</b>	No
<b>Reactivity:</b>	No
<b>Acute:</b>	Yes
<b>Chronic:</b>	Yes

<b>CERCLA Section 302</b>	
<b>Reportable Quantities:</b>	Ammonium hydroxide, 1000 lbs

### SARA 313

This material does not contain any hazardous components exceeding the reporting thresholds established by SARA Title III, Section 313.

### State Right-to-Know


Chemical Name	CAS Number	MA	NJ	PA	RI
Texanol ester alcohol	25265-77-4		X	X	
Di(ethylene glycol) ethyl ether	111-90-0		X	X	
Kaolin	1332-58-7	X	X	X	X
Carbon black	1333-86-4	X	X	X	X
Propylene glycol	57-55-6		X	X	X
Tri(ethylene glycol) bis(2-ethylhexanoate)	94-28-0		X	X	
Ammonium hydroxide	1336-21-6	X	X	X	
4,4-dimethyloxazolidine	51200-87-4		X	X	
Alcohols, C12-15, ethoxylated	68131-39-5		X	X	
Diethylene glycol butyl ether	112-34-5		X	X	

<b>California Proposition 65:</b>	This product contains small amounts of materials known to the state of California to cause cancer or reproductive harm.
-----------------------------------	---

## 16. OTHER INFORMATION

HMIS RATING	
Health:	1*
Flammability:	0
Reactivity:	0
Personal Protection:	--

NFPA CODES



PPE rating has been left intentionally blank. Choose appropriate PPE based upon actual conditions of use.

<b>Revision Indicator:</b>	Revised 3/18/2021
<b>Disclaimer:</b>	The information contained in this Safety Data Sheet (SDS) is provided in good faith and is believed to be accurate as of the effective date listed. The information applies only to the product as provided and may not be valid if combined with other materials. No warranty is implied or given. The user is responsible for complying with all applicable laws and regulations.